

The serial settings for the MICC/P of the Lantronix XPort:

Lantronix XPort Device Server - Mozilla Firefox

http://192.168.16.222/secure/tx_conf.htm

Meistbesuchte Seiten Erste Schritte Aktuelle Nachrichten

Lantronix XPort Device Server

LANTRONIX® Firmware Version: V6.7.0.1
MAC Address: 00-20-4A-D0-19-44

Serial Settings

Channel 1

☐ Disable Serial Port

Port Settings

Protocol: RS232 Flow Control: None

Baud Rate: 57600 Data Bits: 8 Parity: None Stop Bits: 1

Pack Control

☒ Enable Packing

Idle Gap Time: 12 msec

Match 2 Byte Sequence: ☒ Yes ☐ No Send Frame Immediate: ☒ Yes ☐ No

Match Bytes: 0x0D 0x0A (Hex) Send Trailing Bytes: ☒ None ☐ One ☐ Two

Flush Mode

Flush Input Buffer

With Active Connect: ☐ Yes ☒ No

With Passive Connect: ☐ Yes ☒ No

At Time of Disconnect: ☐ Yes ☒ No

Flush Output Buffer

With Active Connect: ☐ Yes ☒ No

With Passive Connect: ☐ Yes ☒ No

At Time of Disconnect: ☐ Yes ☒ No

OK

http://www.lantronix.com/